


GM3402A

SOT-23 場效應晶體管(SOT-23 Field Effect Transistors)


**N-Channel Enhancement-Mode MOS FETs**

N 沟道增强型 MOS 场效应管

**■MAXIMUM RATINGS 最大額定值**

Characteristic 特性參數	Symbol 符號	Max 最大值	Unit 單位
Drain-Source Voltage 漏極 - 源極電壓	$BV_{DSS}$	30	V
Gate- Source Voltage 柵極 - 源極電壓	$V_{GS}$	$\pm 12$	V
Drain Current (continuous) 漏極電流 - 連續	$I_D$	4.5	A
Drain Current (pulsed) 漏極電流 - 脉冲	$I_{DM}$	18	A
Total Device Dissipation 總耗散功率 $T_A=25^{\circ}\text{C}$ 環境溫度為 $25^{\circ}\text{C}$	$P_D$	1400	mW
Junction 結溫	$T_J$	150	$^{\circ}\text{C}$
Storage Temperature 儲存溫度	$T_{stg}$	-55to+150	$^{\circ}\text{C}$

**■DEVICE MARKING 打標**
**GM3402A=X2**



GM3402A

**ELECTRICAL CHARACTERISTICS 電特性**

( $T_A=25^{\circ}\text{C}$  unless otherwise noted 如無特殊說明，溫度為  $25^{\circ}\text{C}$ )

Characteristic 特性參數	Symbol 符號	Min 最小值	Typ 典型值	Max 最大值	Unit 單位
Drain-Source Breakdown Voltage 漏極-源極擊穿電壓( $I_D=250\mu\text{A}, V_{GS}=0\text{V}$ )	$BV_{DSS}$	30	—	—	V
Gate Threshold Voltage 柵極開啓電壓( $I_D=250\mu\text{A}, V_{GS}=V_{DS}$ )	$V_{GS(th)}$	0.6	—	2	V
Diode Forward Voltage Drop 內附二極管正向壓降( $I_S=1\text{A}, V_{GS}=0\text{V}$ )	$V_{SD}$	—	—	1	V
Zero Gate Voltage Drain Current 零柵壓漏極電流( $V_{GS}=0\text{V}, V_{DS}=24\text{V}$ ) ( $V_{GS}=0\text{V}, V_{DS}=24\text{V}, T_A=55^{\circ}\text{C}$ )	$I_{DSS}$	—	—	1 5	$\mu\text{A}$
Gate Body Leakage 柵極漏電流( $V_{GS}=\pm 12\text{V}, V_{DS}=0\text{V}$ )	$I_{GSS}$	—	—	$\pm 100$	nA
Static Drain-Source On-State Resistance 靜態漏源導通電阻( $I_D=4.5\text{A}, V_{GS}=10\text{V}$ )	$R_{DS(ON)}$	—	40	50	$\text{m}\Omega$
Static Drain-Source On-State Resistance 靜態漏源導通電阻( $I_D=3\text{A}, V_{GS}=4.5\text{V}$ )	$R_{DS(ON)}$	—	50	60	$\text{m}\Omega$
Static Drain-Source On-State Resistance 靜態漏源導通電阻( $I_D=2\text{A}, V_{GS}=2.5\text{V}$ )	$R_{DS(ON)}$	—	80	100	$\text{m}\Omega$
Input Capacitance 輸入電容 ( $V_{GS}=10\text{V}, V_{DS}=15\text{V}, f=1\text{MHz}$ )	$C_{ISS}$	—	390	—	pF
Output Capacitance 輸出電容 ( $V_{GS}=10\text{V}, V_{DS}=15\text{V}, f=1\text{MHz}$ )	$C_{OSS}$	—	55	—	pF
Turn-ON Time 開啓時間 ( $V_{DS}=15\text{V}, V_{GS}=10\text{V}, R_{GEN}=6\Omega$ )	$t_{(on)}$	—	3	—	ns
Turn-OFF Time 關斷時間 ( $V_{DS}=15\text{V}, V_{GS}=10\text{V}, R_{GEN}=6\Omega$ )	$t_{(off)}$	—	22	—	ns

Pulse Width $\leq 300\mu\text{s}$ ; Duty Cycle $\leq 2.0\%$



GM3402A

■ TYPICAL CHARACTERISTIC CURVE

典型特性曲线




Figure 1: Output Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Gate-Source Voltage




Figure 5: Gate-Charge Characteristics




Figure 6: Safe Operating Area