




150V N-Channel Enhancement Mode MOSFET

Description

The AP5N15S uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with gate voltages as low as 4.5V. This device is suitable for use as a Battery protection or in other Switching application.



General Features

$V_{DS} = 150V$ $I_D = 5A$

$R_{DS(ON)} < 320m\Omega$ @ $V_{GS}=10V$ (Type: 260m Ω)

Application

Automotive lighting

Load switch

Uninterruptible power supply

Package Marking and Ordering Information

Product ID	Pack	Marking	Qty(PCS)
AP5N15S	SOP-8L	AP5N10S XXX YYYY	3000

Absolute Maximum Ratings ($TC=25^\circ C$ unless otherwise noted)

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	150	V
V_{GS}	Gate-Source Voltage	± 20	V
$I_D @ T_c=25^\circ C$	Drain Current, $V_{GS} @ 10V$	5	A
$I_D @ T_c=100^\circ C$	Drain Current, $V_{GS} @ 10V$	3.1	A
IDM	Pulsed Drain Current ¹	15	A
$P_D @ T_c=25^\circ C$	Total Power Dissipation	2	W
$P_D @ T_A=25^\circ C$	Total Power Dissipation ³	1.1	W
T_{STG}	Storage Temperature Range	-55 to 150	°C
T_J	Operating Junction Temperature Range	-55 to 150	°C
$R_{\theta JA}$	Maximum Thermal Resistance, Junctionambient	70	°C/W
$R_{\theta JC}$	Maximum Thermal Resistance, Junction-case	3.9	°C/W



150V N-Channel Enhancement Mode MOSFET
Electrical Characteristics@T_j=25°C(unless otherwise specified)

Symbol	Parameter	Limit	Min	Typ	Max	Unit
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250μA	150	170		V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250μA	1	1.6	3	V
I _{GSS}	Gate Leakage Current	V _{DS} =0V, V _{GS} =±20V			±100	nA
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =150V, V _{GS} =0V			1	μA
R _{D(S(ON))}	Drain-Source On-Resistance	V _{GS} =10V, I _D = 7A		260	320	mΩ
R _{D(S(ON))}	Drain-Source On-Resistance	V _{GS} =4.5V, I _D = 6A		300	380	mΩ
V _{SD}	Diode Forward Voltage	I _S =1.8A, V _{GS} =0V		0.8	1.2	V
Q _g	Total Gate Charge	V _{DS} =75V, V _{GS} =10V, I _D =10A		17.5		nC
Q _{gs}	Gate-Source Charge			4.5		nC
Q _{gd}	Gate-Drain Charge			4.7		nC
C _{iss}	Input Capacitance	V _{DS} =25V, V _{GS} =0V,f=1MHz		538		pF
C _{oss}	Output Capacitance			55		pF
C _{rss}	Reverse Transfer Capacitance			21		pF
t _{d(on)}	Turn-On Delay Time	V _{DS} =75V, R _L =10.68Ω, V _{GEN} =10V, R _G =6Ω		11.6		ns
t _r	Turn-On Rise Time			9.3		ns
t _{d(off)}	Turn-Off Delay Time			29.3		ns
t _f	Turn-Off Fall Time			3.7		ns

Note :

- 1、The data tested by surface mounted on a 1 inch 2 FR-4 board with 2OZ copper.
- 2、The data tested by pulsed , pulse width \leq 300us , duty cycle \leq 2%
- 3、The power dissipation is limited by 150°C junction temperature
- 4、The data is theoretically the same as I_D and I_{DM} , in real applications , should be limited by total power dissipation.

150V N-Channel Enhancement Mode MOSFET

Typical Characteristics




Fig.1 On Resistance Vs Junction Temperature




Fig.2 On-Resistance Vs. Drain Current




Fig.3 Capacitance




Fig.4 On-Resistance Vs. Gate-to-Source Voltage




Fig.5 Threshold Voltage




Fig.6 On-Region Characteristics

150V N-Channel Enhancement Mode MOSFET




Fig.7 Gate Charge




Fig.8 Body-diode Characteristic




Fig.9 Safe Operating Area






Fig.10 Normalized Maximum Transient Thermal Impedance

150V N-Channel Enhancement Mode MOSFET
Package Mechanical Data-SOP-8L



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.350	1.750	0.053	0.069
A1	0.100	0.250	0.004	0.010
A2	1.350	1.550	0.053	0.061
b	0.330	0.510	0.013	0.020
c	0.170	0.250	0.006	0.010
D	4.700	5.100	0.185	0.200
E	3.800	4.000	0.150	0.157
E1	5.800	6.200	0.228	0.244
e	1.270 (BSC)		0.050 (BSC)	
L	0.400	1.270	0.016	0.050
θ	0°	8°	0°	8°



Recommended Minimum Pads